Solar Panel 220W

- Unique HPBC High Efficiency cells
- Very high efficiency even in lower weather conditions
- Install ready: Including pre-mounted bracket, roof entry & 5 meter cable
- Complete black design
- Reliability guaranteed: up to 25 years warranty



SP220

| Name | SP220 |
|---------|---------------|
| Art.no. | 28110 |
| EAN | 8717809281104 |

| Parameters | | |
|-----------------------------|--------|--|
| Maximum power | 220W | |
| Voltage at PMax (Vmp) | 18.96V | |
| Open circuit voltage (Voc) | 23.15V | |
| Current at PMax (Imp) | 11.60A | |
| Short circuit current (Isc) | 12.28A | |
| Module efficiency | 20.8% | |

| Miscellaneous | |
|-------------------------|----------------------------|
| Solar panel | HPBC High efficiency cells |
| Finishing | Matte film, all black |
| IP class (junction box) | IP67 |
| Dimensions | L1695 x W670 x D40 mm |
| Weight | 12.5 kg |
| Warranty | 5 year |

| Accessories | |
|--------------------|---------------------|
| Battery connection | MC4 |
| Battery wiring MC4 | 1x 5m cable (4 mm²) |

| Package measurements | | |
|----------------------|-----------------------|--|
| Dimensions | L1720 x W700 x D70 mm | |
| Weight | 14.5 kg | |







